

System component: INDUSTRIAL MICRO SD CARD

2 GByte Micro SD Flash Card for ITECNET

- Spider44
- Spider04
- SpiderLine16
- SpiderMike2



Memory card as a voice memory for industrial applications

INDUSTRIAL MICRO SD CARD - SPECIFICATIONS

ATP PART NUMBERS	AF2GUD-2 Serie, swissbit S-450u Serie, Xmore SDU Serie
CAPACITIES	2 GB
CONNECTOR PIN	8 Pins
DURABILITY	Waterproof: Yes Dust Proof: Yes ESD Proof: Yes Extreme Temp: Yes
ELECTRICAL CHARACTERISTICS	Supply voltage SD: 2.7V-3.6V Low Power Consumption (<50mA) Clock speed: 50Mhz max.
ENVIRONMENTAL CHARACTERISTICS	Operating Temp: 0C to 70C Storage Temp: 0C to 70C Humidity: 8 - 95 % non-condensing Vibration: 15Gs peak-to-peak Max Shock: 1000G
RELIABILITY	Number of insertions: 10,000 minimum Data retention: 10 years Endurance: >10,000 cycles (read/write and erase)
PHYSICAL CHARACTERISTICS	Length: 11mm +/- 0.1mm Width: 15mm +/- 0.1mm Thickness: 1.0mm +/- 0.1mm Weight: 0.4 g max

All information without guarantee. Subject to technical changes.